



Client _____ Quantity _____
Project _____ Position _____

Function oven

Model: GERU411SP

Cod: NP01041021008

Technical data


Number of pans:	4
Pans size (mm):	GN 1/1
Tray centre distance (mm):	70
Number of fans:	2
Fan speed:	1
Dimensions (mm):	724 x 730 x 597
Net weight (kg):	48
Volume (m3):	0,320
Chamber size (mm):	618 x 435 x 326
Electric power (kW):	3,5
Voltage (V):	220-240
Power supply (A):	16
Phases:	1N
Cable section (mmq):	3G1,5
Frequency (Hz):	50-60
Cold water connection:	3/4"
Cold water pressure (bar):	Max 5 bar
Drain size (mm):	30
Packing dimensions (mm):	745 x 770 x 771
Chamber size (mm):	618 x 435 x 326
Gross weight (kg):	52
Gross volume (m3):	0,442

Features

Oven type:	Convection
Control:	Programmable
Grill:	Disponibile
Steam:	Direct
Steam management:	Pressure
Temperature range:	50°C - 300°C
Door:	Drop down
Cooking chamber bottom:	AISI 430 mirror finish
Range timer:	1' - 120'
Flue:	Always open

Programmable electric convection ovens with humidifier and grill. Capacity 4 trays GN 1/1. Cooking chamber with rounded corners, welded without visible welding. Adjustable height of the feet. Removable grid shelves with distance between trays of 70 mm. Door with wide glass surface equipped with air channel for the external glass ventilation, which further limits the temperature on the external surface. Door handle in plastic material, highly resistant to shocks and temperatures. Silicone gasket inserted in the front of the chamber, with maximum seal capacity, avoiding temperature drops. Heating through high efficiency coated heating elements. Timer from 1' to 120' (plus infinite position). Manual button humidifier. Temperature control in the cooking chamber from 50 °C to 300 °C. 2 fans. Wide air flow channels of the chamber that allows a perfect cooking uniformity, both in conditions of scarce and full load. Folding opening of the internal glass. Control panel of all the functional parts placed on the bottom side of the oven. Safety thermostat in the cooking chamber to avoid dangerous high temperatures. Water inlet for the humidifier control. Internal lighting positioned on the left side of the cooking chamber. Automatic programmable steam injection. Electric power 3,5 Kwatt - 220-240V/1N+G 50/60 Hz

Technical draw



E: Electric connection

D: Drain for water

H2O: Water inlet 3/4"