Клиент _____ Количество _____

Проект _____ Позиция _____



Печь Function

Модель: BER443ECO **Код:** NP01041022006

Технические данные


Количество противней:	4
Шаг установки противней (мм):	433x333
Шаг установки противней (мм):	70
Количество вентиляторов:	2
Скорость вентилятора:	1
Габариты (мм):	557 x 640 x 563
Вес (кг):	37
Объём ($м^3$):	0,200
Размеры камеры (мм):	452 x 371 x 326
Электрическая мощность (кВт):	2,8
Электропитание (V):	220-240
Электропитание (A):	12,5
Количество фаз:	1N
Сечение кабеля ($мм^2$):	3G1,5
Частота (Гц):	50-60
Габариты с упаковкой (мм):	590 x 680 x 788
Размеры камеры (мм):	452 x 371 x 326
Масса брутто (кг):	40
Объём брутто ($м^3$):	0,320

Характеристики

Тип печи:	Конвекция
Панель управления:	Электромеханический
Функции:	Приготовление в режиме конвекции
Пар:	Прямой режим
Управление парообразованием:	С таймером
Диапазон температур:	50°C - 300°C
Дверь:	Откидная дверца
Дно камеры приготовления:	AISI 430 полированная поверхность
Диапазон таймера:	1' - 120'
Дымоход:	Всегда открытый

In order to constantly offer the best possible products we reserve the right to make changes on technical specifications without incurring any obligation for equipment previosly or subsequently sold.

Технический чертеж



E : Alimentazione elettrica

In order to constantly offer the best possible products we reserve the right to make changes on technical specifications without incurring any obligation for equipment previosly or subsequently sold.